

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number
WO 2005/069339 A1

(51) International Patent Classification⁷: **H01J 29/00**,
H04N 9/29, H01J 29/70

(21) International Application Number:
PCT/US2004/042457

(22) International Filing Date:
17 December 2004 (17.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/534,458 6 January 2004 (06.01.2004) US

(71) Applicant (for all designated States except US): **THOM-
SON LICENSING S. A.** [FR/FR]; 46 Quai A. Le Gallo,
F-92100 Boulogne-Billancourt (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GOROG, Istvan**
[US/US]; 1275 Wheatland Avenue, Lancaster, Pennsylva-
nia 17601 (US). **BARBIN, Robert, Lloyd** [US/US]; 2656
Riceville Drive, Henderson, Nevada 89052 (US).

(74) Agents: **TRIPOLI, Joseph, S.** et al.; 2 Independence Way,
Suite #200, Princeton, NJ 08540 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: MAGNETIC FIELD COMPENSATION APPARATUS FOR CATHODE RAY TUBE



(57) **Abstract:** A cathode ray tube (CRT) (1) having a glass envelope (2) is disclosed. The glass envelope is formed of a rectangular faceplate panel (3) and a tubular neck (4) connected thereto by a funnel (5). An electron gun (13) is positioned in the neck for directing electron beams toward the faceplate panel. A yoke (14) is positioned in the neighborhood of the funnel-to-neck junction. The yoke has windings configured to apply a horizontal deflection yoke field and a vertical deflection yoke field to the beams. At least one magnetic field sensor (17) is located near the glass envelope for sensing an ambient magnetic field environment of the CRT. A controller receives a signal from the magnetic field sensor. Register correction coils are mounted in the vicinity of the neck and are dynamically controlled by the controller to shift the beams. Quadrupole coils (16) are applied to the neck and have adjacent poles of alternating polarity such that the resultant magnetic field being dynamically controlled by the controller based on the magnetic field sensor signal moves outer ones of the beams to correct the misconvergence caused by the register correction.

WO 2005/069339 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.